

TUBI API 5L - GRADO B



Diametro mm.		Spessore (mm.)	Peso Kg./mt	Identificazione		
Nominale in.	Esterno mm.			CorrISP. norme API	Standard x-strong xx-strong	numero di sched.
1/8	10,3	1,73	0,36	5L	STD	40
		2,41	0,46	5L	XS	80
1/4	13,7	2,24	0,63	5L	STD	40
		3,02	0,80	5L	XS	80
3/8	17,1	2,31	0,85	5L	STD	40
		3,20	1,10	5L	XS	80
1/2	21,3	2,77	1,27	5L	STD	40
		3,73	1,62	5L	XS	80
		4,76	1,95	--	--	160
		7,47	2,55	5L	XXS	--
3/4	26,7	2,87	1,68	5L	STD	40
		3,91	2,19	5L	XS	80
		5,56	2,89	--	--	160
		7,82	3,63	5L	XXS	--
1"	33,4	3,38	2,50	5L	STD	40
		4,55	3,23	5L	XS	80
		6,35	4,23	--	--	160
		9,09	5,45	5L	XXS	--
1" 1/4	42,2	3,56	3,38	5L	STD	40
		4,85	4,46	5L	XS	80
		6,35	5,60	--	--	160
		9,70	7,76	5L	XXS	--

TUBI API - ASTM



Diametro mm.		Spessore (mm.)	Peso Kg./mt	Identificazione		
Nominale in.	Esterno mm.			CorrISP. norme API	Standard x-strong xx-strong	numero di sched.
1" 1/2	48,3	3,68	4,05	5L	STD	40
		5,08	5,41	5L	XS	80
		7,14	7,33	--	--	160
		10,16	9,55	5L	XXS	--
2"	60,3	3,91	5,44	5L 5LX	STD	40
		5,54	7,47	5L 5LX	XS	80
		8,74	11,11	--	--	160
2" 1/2	73,0	5,16	8,68	5L 5LX	STD	40
		7,01	11,41	5L 5LX	XS	80
		9,52	14,91	--	--	160
3"	88,9	5,49	11,28	5L 5LX	--	40
		7,62	15,25	5L 5LX	--	80
		11,13	21,30	5L 5LX	--	160
3" 1/2	101,6	5,74	13,56	5L 5LX	--	40
		8,08	18,62	5L 5LX	--	80
4"	114,3	6,02	16,06	5L 5LX	--	40
		8,56	22,29	5L 5LX	--	80
		11,13	28,25	5L 5LX	--	120
		13,49	33,51	5L 5LX	--	160